CARE & MAINTENANCE

Autex Interior Acoustics and Quietspace® products are extremely durable and require little attention to maintain their good looks. Light vacuuming on a regular basis will prevent dust build up and most marks can be cleaned with a mild detergent solution followed by rinsing and blotting. Stains should be dealt with according to the chart below. Before carrying out a proposed cleaning method, apply to a concealed section to ensure it will not affect the adhesive or product. Avoid severe abrasion. Spot clean only. Vacuum to restore pile, but do not use a stiff brush.

NB: We do not recommend using solvent-based solutions on Autex Interior Acoustics and Quietspace® products.

STAIN	TRE	ATMEN	NT GU	IIDE
Blood	A	С		
Burn/Scorch Mark	K	C		
		_	_	
Chewing Gum	В	С	D	I
Chocolate	В	С	D	
Cooking Oils	В	С	D	
Crayon/Colour Markers	В	С	D	
Drinks (cola, tea, juices, beer etc.)	Α	С		
Dust/Dirt	Vacuum, then J or C			
Excrement	В	С		
Grass	С			
Grease	В	С	D	
Ink (ballpoint)	D	Е		
Ink (fountain)	Α	С		
Lipstick	В	С	D	Е
Mildew	С			
Milk	Α	Е		
Mud	В	С		
Nail Polish	Α	G		
Oil	В	С	D	
Paint (water based)	Α	С	F	
Paint (oil based)	Α	С	D	Н
Sauces	В	С	D	
Shoe Polish	В	С	D	
Urine	Α	С		
Vomit	Α	С	D	
Wine	Α	Add	Salt	C
	, ,	,	- an	0

KEY

- A Mop up excess as soon as possible with a sponge or cloth.
- B Remove surplus with a knife edge or appropriate instrument.
- C Sponge with a solution of carpet shampoo working from well outside the stain in a circular motion towards the centre (this avoids spreading the stain). Sponge afterwards with clean warm water and mop excess moisture with a clean dry cloth or sponge. Allow to dry then brush gently with a soft brush. If any stain remains, sponge with a solution of one part household bleach to six parts clear water. Thoroughly rinse after treatment.
- D Lightly sponge with household dry cleaning fluid and blot. Apply sparingly, as the substance may have an adverse effect on the adhesive.
- E Sponge with methylated spirits and blot dry.
- F Lubricate the stain with glycerine or petroleum jelly.
- G Apply nail polish remover. The nail polish remover should not include lanolin or be of a greasy nature.
- H Sponge with turpentine (or substitute).
- I Freeze with ice cubes and scrape away while cold.
- J Clean with regular extractive carpet cleaner (if possible).
- K Use circular cutter and remover damaged portion.

 Re-glue new piece into place.

SPECIALIST FINISHES

Autex recommends that you contact professional cleaning experts should you require further assistance with the cleaning and maintenance of Autex Interior Acoustic products. Please talk to your Autex Account Manager for advice on local commercial cleaning contractors.

Autex offers these recommendations in good faith, however, we cannot be responsible for unsatisfactory results from the proposed treatments.

Autex Industries Ltd

702-718 Rosebank Rd Private Bag 19988 Avondale 1746, Auckland New Zealand

Freephone **0800 428 839**Phone **+64 9 828 9179**Fax **+64 9 828 5810**

www.autex.co.nz

Autex Pty Ltd

166 Bamfield Road PO Box 5099 West Heidelberg, Melbourne VIC 3081, Australia Freephone **1800 678 160**

Freephone 1800 678 160
Phone +61 3 9457 6700
Fax +61 3 9457 1020

www.autex.com.au

Autex Acoustics Ltd

Unit 1 Alchemy Industrial Est. Platinum Court, Alchemy Way Liverpool, L33 7XN United Kingdom

Phone +44 151 294 3236 Fax +44 151 546 0863

www.autexacoustics.co.uk

Autex Acoustics LLC

California USA

Phone +1 805 407 9256 Fax +1 805 457 8932

www.autexacoustics.com